

Part Number Code Logic

V-70631 - CA - XXX - X

A B C D

A: Ground Power Assembly

B: CA = Cable Assembly

C: Length of Cable Assembly (end to end)

EX: 360 = 360 Inches or M10 = 10 Meters

D: Variables Such as Single Jacketed Cable, Alternate Keying, Color coding, Multi Hole Grommet




Explosionproof Receptacle: GDT-B1528-42SL-XX.
See Product Data Sheet: PDS-GD-SD-ATR
for Certifications, Grommet & Bill of Materials.

Explosionproof Plug: GDT-D1028-42PL-XX.
See Product Data Sheet: PDS-GD-SD-PLUG
for Certifications, Grommet & Bill of Materials.

The "XX" at the End of the Part Numbers will
be Replaced with a Grommet Code to Fit
Cable Diameter.

Plug and Receptacle are Available with Color
Coding to Assure Proper Mating

Cable Assembly Consists of (4) 1/0 AWG
Conductors and (1) 2 Conductor #12 AWG Cable.
Supports are Located Every 3 Feet.

REV: A	WTN BY: JACK NELLIGAN	DOCUMENT TITLE: CABLE ASSEMBLY GROUND POWER EXTENSION CORD	 Vantage Technology LLC 4675 South Windermere Street Englewood, Colorado USA 80110 Phone: 303-761-2121 ~ Fax: 303-789-4215 Email: service@vantagexp.com ~ Website: www.vantagexp.com	SHEET: 1 OF 1
	CHK BY: JACK NELLIGAN			
	ENG BY: DARRIN J. LOMBARD			
	ATEX: JOHN NORDECK			
	RELEASE DATE: 12/16/05			
APPLICATION DATA SHEET		DOCUMENT NUMBER: ADS-V-70631		